

QUICK•STEP® COMBI FLOOR PLUS

ALL IN ONE! Realistic sound. Moisture protection. Embossed self-leveling.

It's everything you and your customers demand – in one quality underlayment.

As the leader in laminate flooring technology, Quick•Step® knows that a floor is only as good as what is underneath it. Our unique Combi Floor Plus three-in-one underlayment combines the very best features into one quality underlayment.

It's the perfect solution for any floating-floor system, combining the quality features that result in fewer callbacks and more satisfied customers.



QUICK•STEP® COMBI FLOOR PLUS



REALISTIC SOUND

» Premium quality pad offers superior sound-absorption and reduces the hollow tapping noise — produces a sound that is close to actual hardwood and transmits less sound to adjacent rooms and rooms below.

MOISTURE PROTECTION

» Preattached moisture barrier with attached overlapping lip and tape helps protect floor from moisture damage and is easy to install.

EMBOSSSED SELF-LEVELING

» Embossed foam compensates for uneven subfloors — for better sound and protection of the floor.

AND MORE!

- » Material helps prevent mold, mildew and bacteria growth and is nonallergenic.
- » Offers thermal insulation and is safe with underfloor heating.
- » 25-year Quick•Step® warranty.

Sound Transmission Loss	XX
Sound Transmission Class (STC)	54
Impact Sound Transmission	XX
Impact Insulation Class (IIC)	60

amazing what a floor can do™



Dealer Imprint

QUICK•STEP® COMBI FLOOR PLUS

ALL IN ONE! Realistic sound. Moisture protection. Embossed self-leveling.

PROPERTY	SPECIFICATION
Materials	Cross-linked polyolefin foam
Standard Roll Size	161 sq. ft.
Part Number	QSUDLDRUCO15
Foam Color/Film	White/Clear
Thickness	0.08"
Moisture Barrier	4.93 mil top
Mold- and Mildew-Resistant	Yes
Tensile Strength (psi)	Length: 78/Width: 64
Water Absorption (lbs./sq.ft.)	<0.00036
Water Vapor Transmission (Perm Rating)	0.06
Elongation to Break (%)	Length: 180/Width:160
Tear Resistance lbs./in.	Length: 78/Width: 64
R Value	3.19/in.
Compression Strength (psi)	X.XX
(ASTMD3575)	21
Working Temperature (F)	-326
Chemical Resistance	Good
Sound Transmission Loss	XX
Sound Transmission Class (STC)	54
Impact Sound Transmission	XX
Impact Insulation Class (IIC)	60
Rolls Per Box	12
Boxes Per Pallet	3
Pallets Per Truck	48
Rolls Per Truckload	1,728



With a heritage of style and innovative technology, Quick•Step® is known for transforming both the style and substance of today's flooring. The direct-pressure laminate technology that we pioneered is the industry standard. Our patented Uniclic® locking system revolutionized the industry. And our specially formulated underlaments set the standard for quality performance, no matter what floors are installed on top of them.

Quick•Step®
7834 C.F. Hawn Freeway
Dallas, TX 75217
888.387.9882