

QUICK·STEP® UNISOUND COMBI FLOOR

Unbeatable sound quality plus an extra-thick moisture barrier.

When you and your customers won't settle for anything but the best.

From the leader in laminate flooring technology comes our finest underlayment product. The Quick·Step® Unisound Combi Floor combines all the premium features you and your customers demand. Developed with a special cross-linked foam, its scientifically engineered acoustical properties absorb reflective noise in the room. This creates a warm, realistic sound that will result in fewer callbacks from homeowners.

It's the ultimate solution for any floating-floor system, creating a beautiful floor that results in fewer callbacks and more satisfied customers.



QUICK·STEP® UNISOUND COMBI FLOOR



Our best at reducing hollow tapping noise — produces a sound that is very close to actual hardwood.

- » Provides a self-leveling effect — to compensate for uneven subfloors.
- » Extra-thick, preattached moisture barrier with attached overlapping lip and tape — helps protect floors from moisture damage and is easy to install.
- » Material helps prevent mold, mildew and bacteria growth and is nonallergenic.
- » Offers thermal insulation and is safe for underfloor heating.
- » Installs over all subfloors — including cement and plywood.
- » 25-year Quick·Step® warranty.

Sound Transmission Loss	XX
Sound Transmission Class (STC)	54
Impact Sound Transmission	XX
Impact Insulation Class (IIC)	60

amazing what a floor can do™



Dealer Imprint

QUICK·STEP® UNISOUND COMBI FLOOR

Unbeatable sound quality plus an extra-thick moisture barrier.

PROPERTY	SPECIFICATION
Materials	Cross-linked polyolefin foam
Standard Roll Size	161 sq. ft.
Part Number	QSUDLDRUCO15
Foam Color/Film	White/Clear
Thickness	0.08"
Moisture Barrier	4.93 mil top
Mold- and Mildew-Resistant	Yes
Tensile Strength (psi)	Length: 78/Width: 64
Water Absorption (lbs./sq.ft.)	<0.00036
Water Vapor Transmission (Perm Rating)	0.06
Elongation to Break (%)	Length: 180/Width:160
Tear Resistance lbs./in.	Length: 78/Width: 64
R Value	3.19/in.
Compression Strength (psi)	X.XX
(ASTMD3575)	21
Working Temperature (F)	-326
Chemical Resistance	Good
Sound Transmission Loss	XX
Sound Transmission Class (STC)	54
Impact Sound Transmission	XX
Impact Insulation Class (IIC)	60
Rolls Per Box	12
Boxes Per Pallet	3
Pallets Per Truck	48
Rolls Per Truckload	1,728



With a heritage of style and innovative technology, Quick·Step® is known for transforming both the style and substance of today's flooring. The direct-pressure laminate technology that we pioneered is the industry standard. Our patented Uniclic® locking system revolutionized the industry. And our specially formulated underlayments set the standard for quality performance, no matter what floors are installed on top of them.

Quick·Step®
7834 C.F. Hawn Freeway
Dallas, TX 75217
888.387.9882